



Switch to

RAYMINOUS™
Tuning the power

High efficient & Eco-friendly LED Lightings



RAYMINOUSTM
Tuning the power

RAYMINOUS LED Quality Lighting

Rayminous Power Solutions Pvt. Ltd.'s quality lighting products stand for efficient heat extraction, withstandable power fluctuations, eco-friendliness, reliability and cost effectiveness with state-of-the art technology.

Long life and zero maintenance.

Green lighting solutions with dedicated customer service.



LED Office Lighting

OFFICE LIGHTS : Cruise
 Suitable for recessed mounting. Cool White (CW) Luminary.

Lamp Type	Item Description	Order Code	MRP
30W AC	SQ2'X2'PANEL LGT	RM0030WOFC01	13,500.00
40W AC	SQ2'X2'PANEL LGT	RM0040WOFC02	16,900.00
50W AC	SQ2'X2'PANEL LGT	RM0050WOFC03	18,500.00



TECHNICAL SPECIFICATION

Wattages : 30/40/50W
 Light Source : Cree/Nichia/Lumileds/Osram
 Optics : Designed to meet office lighting standard
 Voltage Range : 85V to 275V
 Elec. Details : HPF>0.98, Efficiency>85%, VThd<5%, Athd<10%
 IP Rating : IP-65
 Material Used : Powder coated CRCA sheet housing
 Designed with opal diffuser
 Dimension : 595x595x70 mm



LED Down Lighting

TECHNICAL DETAILS

General

Application	: Indoor
Working Temperature (°C)	: -5 to 55
Working Humidity (RH)	: 10%-90%

LED Data

LED make	: Nichia/Osram/Everlight
Dispersion Angle in degrees	: 120
Colour Temp (K)	: 5500-6700
CRI	: >70

Electrical Parameter

Input Voltage in Volts (90V to 300V)	: 230
Power Factor @Full Load	: >0.9
THD (%) @Full Load	: <20%
Protection provided	: Over Voltage, Surge, Short Circuit, Open Circuit, Output Reverse Polarity
Fixture/heatsink material	: Aluminium Pressure Die

Down Light Round : RAPID

Cool White (CW) Luminary

Suitable for recessed mounting. This model as a powder coated metal outer frame and side channel heat sink for better performance with very low power consumption and long lasting life.

Lamp Type	Item Description	Order Code	MRP
4W AC LED CW	White Coated Fixture	RM004WDL01	1,530.00
7W AC LED CW	White Coated Fixture	RM007WDL02	2,050.00
12W AC LED CW	White Coated Fixture	RM0012WDL03	2,790.00
15W AC LED CW	White Coated Fixture	RM0015WDL04	2,600.00
20W AC LED CW	White Coated Fixture	RM0020WDL05	3,500.00



Down Light Round Ultra Slim Lite : CYON

Cool White (CW) Luminary

Lamp Type	Item Description	Order Code	MRP
6W AC LED CW	White Coated Fixture	RM006WSDL011	2,100.00
12W AC LED CW	White Coated Fixture	RM0012WSDL012	2,990.00
18W AC LED CW	White Coated Fixture	RM0018WSDL013	3,950.00



Down Light Round Ultra Slim Lite : CYON-R

Warm White (WW) Luminary

Lamp Type	Item Description	Order Code	MRP
3W AC LED WW	White Coated Fixture	RM003WSDL021	1,550.00
6W AC LED WW	White Coated Fixture	RM006WSDL022	2,100.00
12W AC LED WW	White Coated Fixture	RM0012WSDL023	2,990.00




Down Light Square Ultra Slim Panel : SLEEK

Cool White (CW) Luminary

MINOR series suitable for recessed mounting. This model has a powder coated metal outer frame and side channel heat sink for better performance with very low power consumption and long life.


Lamp Type	Item Description	Order Code	MRP
3W AC LED CW	White Coated Fixture	RM003WSDL031	1,550.00
6W AC LED CW	White Coated Fixture	RM006WSDL032	2,100.00
12W AC LED CW	White Coated Fixture	RM0012WSDL033	2,990.00
18W AC LED CW	White Coated Fixture	RM0018WSDL034	3,950.00



Down Light Square Ultra Slim Panel : SLEEK-J

Warm White (WW) Luminary

Lamp Type	Item Description	Order Code	MRP
3W AC LED WW	White Coated Fixture	RM003WSDL041	1,550.00
6W AC LED WW	White Coated Fixture	RM006WSDL042	2,100.00
12W AC LED WW	White Coated Fixture	RM0012WSDL043	2,990.00
18W AC LED WW	White Coated Fixture	RM0018WSDL044	3,950.00





LED Tube Lighting

Tube Light T8/T5 : SYNON
Cool White (CW) Luminary

Lamp Type	Item Description	Order Code	MRP
9W AC LED CW	2 ft tube light fixture	RM009WTL01	2,150.00
18W AC LED CW	4 ft tube light fixture	RM0018WTL02	3,000.00
22W AC LED CW	4 ft tube light fixture	RM0022WTL03	3,800.00
28W AC LED CW	4 ft tube light fixture	RM0028WTL04	4,500.00



Tube Light Slim T5 : VEIN
Cool White (CW) Luminary

Lamp Type	Item Description	Order Code	MRP
20W AC LED CW	4 ft tube light fixture	RM0020WSTL I I	3,800.00



Bulb

Lamp Type	Item Description	Order Code	MRP
4W AC	LED CW Bulb	RM004WB01	1,090.00
6W AC	LED CW Bulb	RM006WB02	1,390.00
8W AC	LED CW Bulb	RM008WB03	2,000.00
10W AC	LED CW Bulb	RM0010WB04	2,290.00



TECHNICAL DETAILS

General

Application	: Indoor
Working Temperature (°C)	: -5 to 55
Working Humidity (RH)	: 10%-90%

LED Data

LED Type	: Low Power LED
LED Make	: Nichia/Osram/Everlight
Dispersion Angle in degrees	: 120
Colour Temp (K)	: 5500-6700
CRI	: >70

Electrical Parameter

Input Voltage in Volts (90V to 300V)	: 230
Power Factor @Full Load	: >0.9
THD (%) @Full Load	: <20%
Protection provided	: Over Voltage, Surge, Short Circuit, Open Circuit, Output Reverse Polarity
Fixture/heatsink material	: Aluminium Extrusion



LED Street Lighting

AC Street Lights : SIGMA

Cool White (CW) Luminary

New generation energy saving and environment friendly.

Lamp Type	Item Description	Order Code	MRP
30W AC	LED Street	RM0030WS01	8,400.00
40W AC	LED Street	RM0040WS02	10,700.00
50W AC	LED Street	RM0050WS03	12,800.00



Technical Specification

Wattages : 30/40/50W
 Light Source : Cree/Nichia/Lumileds/Osram
 Optics : Designed to meet road lighting
 Voltage Range : 85V to 275V
 Power Rating : HPF>0.98, Efficiency>85%, VThd<5%, Athd<10%
 IP Rating : IP-66
 Material Used : Aluminium pressure die cast body



AC Street Lights High Power : GRASSY

Cool White (CW) Luminary

New generation energy saving and environment friendly long life, Aluminium die-cast heat sink for better performance with very low power consumption.

Lamp Type	Item Description	Order Code	MRP
40W AC	Street Light	RM040WGS01	11,900.00
50W AC	Street Light	RM050WGS02	19,200.00
60W AC	Street Light	RM060WGS03	23,500.00
70W AC	Street Light	RM070WGS04	26,500.00
100W AC	Street Light	RM0100WGS05	35,900.00
120W AC	Street Light	RM0120WGS06	45,500.00
150W AC	Street Light	RM0150WGS07	54,500.00



TECHNICAL SPECIFICATION

Wattages : 50/60/70/100/120/150W
 Light Source : Cree/Nichia/Lumileds/Osram
 Optics : Designed to meet office lighting standard
 Voltage Range : 85V to 275V
 Power Rating : HPF>0.98, Efficiency>85%, VThd<5%, Athd<10%
 IP Rating : IP-66, IP-65 (100/120/150W)
 Material Used : Aluminium pressure die cast body
 Toughened glass diffuser
 Dimension : 384x192x51 mm, 573x243x69 mm (100/120/150W)

LED Solar Street Lighting



Solar Powered LED Street Lights : ALEXA


RAYMINOUS has designed and developed Solar based lighting systems for long lasting performance with uniform brightness.

Features	Pack 1	Pack 2	Pack 3	Pack 4
Wattage	20W	24W	40W	60W
CCU	12V/10 amp	12V/10 amp	12V/20 amp	24V/10 amp
PV Panel	74W	100W	150W	240W
Battery	75Ah	100Ah	150Ah	240Ah
Pole(mtr)	5 mtr	5 mtr	6 mtr	7 mtr
Autonomy	2 Days	2 Days	2 Days	2 Days
Order Code	RM020WST01	RM020WST02	RM020WST03	RM020WST04
MRP	55,000.00	68,500.00	95,700.00	1,45,000.00

- Variants available with different models of street lights
- Custom designing available
- MS & GI Pole available with anti rust treated and powder coated
- Battery available with SMF & Tubular options
- The MRP does not include transportation charges & installation charges

DC Solar Lantern Lights

Lamp Type	Item Description	Order Code	MRP
2.2W DC	Lantern	RM004WB01	3,500.00
3W DC	Lantern	RM006WB02	4,000.00





LED Flood Lighting

Flood Lights : FOCUS
Cool White (CW) Luminary

Lamp Type	Item Description	Order Code	MRP
10W AC	Flood light	RM0010WFD01	6,500.00
20W AC	Flood light	RM0020WFD02	8,900.00
30W AC	Flood light	RM0030WFD03	10,900.00
40W AC	Flood light	RM0040WFD04	13,500.00
50W AC	Flood light	RM0050WFD05	18,600.00
60W AC	Flood light	RM0060WFD06	20,700.00
70W AC	Flood light	RM0070WFD07	22,800.00
80W AC	Flood light	RM0080WFD08	24,900.00
90W AC	Flood light	RM0090WFD09	26,500.00
100W AC	Flood light	RM0100WFD010	32,600.00



RAYMINOUS has designed to light up the areas like Stadiums, Industrial areas & many more with Flood lights engined by the new generation LED platform, with different class of secondary optics based on applications & reliable high quality driver technology and innovative thermal management design.

TECHNICAL SPECIFICATION

Wattages	: 10/20/30/40/50/60/70/80/90/100W
Light Source	: Cree/Nichia/Lumileds/Osram
Optics	: Designed with wide spread lens
Voltage Range	: 85V to 275V
Elec. Details	: HPF>0.98, Efficiency>85%, VThd<5%, Athd<10%
IP Rating	: IP-65
Material Used	: Aluminium pressure die cast body Toughened glass diffuser
Dimension	: 10/20W 180x140x105 mm 30/40W 225x185x125 mm 50/60/70W 285x235x140 mm 90/100W 285x360x100 mm

RAYMINOUS™
Tuning the power



PLEDGE
for
SAFETY & ENVIRONMENT

RAYMINOUSTM
Tuning the power

• BANGALORE • VISAKHAPATNAM • HYDERABAD
Email : info@rayminous.com Website : www.rayminous.com